

SILICON CARBIDE WARNING TACTILE

P5
GRIP

PRODUCT CODES: DESCRIPTION:

AT212 SPIKED

RANGE	Warning Tactile
DESIGN	Classic Silicon Carbide
MATERIAL	316 marine grade stainless steel with silicon carbide infill
LOCATION	Indoor or outdoor
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm



AT212 Yellow insert also available

FEATURES & BENEFITS

Hard wearing silicon carbide inserted into the horizontal face with a smooth machined outer edge

Complies with the NCC [D4D9 Tactile Indicators] and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Identifiable by the unique "double lip" design, providing a distinct advantage when it comes to high slip resistance

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST AS 4586 APPENDIX A: Wet Pendulum Test

FOUR S 96 SLIDER = 79 **CLASS** = P5

TRL 55 SLIDER = 77 **CLASS** = P5


LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the TA TGSI, see: AS/NZS 1428.4.1:2009.

TEST AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3

LIGHT REFLECTANCE VALUE / WET = 4.00

LIGHT REFLECTANCE VALUE / DRY = 5.20



CODE AT212

FIXING Drill and pressure fit
(M8 x 25mm hole)