


URBAN EDGING 10X65X5MM (YELLOW)

PRODUCT CODES: DESCRIPTION:

P5
GRIP

AT-SN 02 NATURAL ANODISED
Yellow silicon carbide infill

RANGE	Stair Nosing & Edging
DESIGN	Urban
MATERIAL	6063 T5 extruded aluminium alloy with silicon carbide infill
LOCATION	Indoor or outdoor



FEATURES & BENEFITS

Continuous band of hard wearing, solid silicon carbide inserted into aluminium extrusions designed in Australia

Available in an exclusive premium quality angle profile

Suitable for all stable finished outdoor or indoor surfaces and substrates

Complies with the NCC (D4D4 Parts of buildings to be accessible) where stated and Disability (Access to Premises—Buildings) Standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

SLIP RESISTANCE TESTING


Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= 58 CLASS = P5

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the AT EDGING, see: AS 1428.1:2009.

TEST	AS 1428.1 APPENDIX B PARAGRAPH B3
LIGHT REFLECTANCE VALUE / WET	= 33.27
LIGHT REFLECTANCE VALUE / DRY	= 34.65



CODE	AT-SN 02
SIZE	H10 x W65 x T5 - L3200mm